

HYUNDAI (USA) ELANTRA COUPÉ JK

ELANTRA COUPÉ 2.0 GDI (2013-2014)



MOTOR Nu

Kapacitet: 4 liter (Servicepåfyldning), Kapacitet: 4,5 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 7500 mil/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 3750 mil/ 6 måneder

TRANSAKSEL AUTOMATISK A6MF1-1 6/1

Kapacitet: 7,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

Skift alle 60000 mil

TRANSAKSEL MANUEL M6CF3-1 6/1

Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 37500 mil/ 30 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 37500 mil/ 30 måneder, skift alle 75000 mil

HYUNDAI (USA) ELANTRA COUPÉ JK

ELANTRA COUPÉ 2.0 GDI (2013-2014)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 30000 mil/ 24 måneder

KØLESYSTEM

Kapacitet: 5,9 liter (med automatisk transaksel), Kapacitet: 6 liter (med manuel transaksel)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 30000 mil/ 24 måneder

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 120000 mil/ 120 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 90-110 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 475-525 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.