HYUNDAI (USA) SANTA FE DMA/NC SANTA FE SPORT 2.0 T-GDI (2013-2013)



ENGINE Theta II Turbo Capacity: 5,5 liter (Dry fill), Capacit	y: 4,6 liter (Service fill), Filter capacity: 0,4 li	ter
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30
Change every 5000 miles/ 6 month	IS	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30
Change every 3000 miles/ 3 month	ns	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30
Change every 3000 miles/ 6 month	, JS	'

TRANSAXLE AUTOMATIC A6LF2 6/1 Capacity: 7,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 60000 miles	·

HYDRAULIC BRAKE SYSTEM Capacity: 0,7-0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 30000 miles/ 24 months		

HYUNDAI (USA) SANTA FE DMA/NC SANTA FE SPORT 2.0 T-GDI (2013-2013)



COOLING SYSTEM Capacity: 9,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 30000 miles/ 24 mon	nths	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 60000 miles/ 60 mor	iths	

AIRCONDITIONING COMPRESSOR Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 575-625 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.