HYUNDAI (EU) EQUUS / CENTENNIAL VI EQUUS / CENTENNIAL 3.8 V6 GDI (248 KW)



(2014-2016)

ENGINE Lambda Capacity: 6 liter (Dry fill), Capacity: 5,5 liter (Service fill), Filter capacity: 0,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30	
Check every 500 km, change every 15000) km/ 12 months		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30	
Check every 500 km, change every 7500	km/ 6 months		

DIFFERENTIAL REAR Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 48 months/ 60000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

TRANSMISSION AUTOMATIC A8LR1 8/1 Capacity: 9,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 90000 km	·

Check every 60000 km/48 months, change every 120000 km

HYUNDAI (EU) EQUUS / CENTENNIAL VI EQUUS / CENTENNIAL 3.8 V6 GDI (248 KW)



(2014-2016)

HYDRAULIC BRAKE SYSTEM Capacity: 0,7-0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 15000 km/ 12 months	·

COOLING SYSTEM Capacity: 10,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change avery 20000 km/24 month		'	

Change every 30000 km/24 months

Coolant SP 15+	Coolant SP 12		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
First change only		Moderate	
USE		CLIMATE	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.