

HYUNDAI (EU) EQUUS / CENTENNIAL VI

EQUUS / CENTENNIAL 4.6 V8 MPI (2010-2011)



ENGINE Tau
Capacity: 6,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth LSP Ultra 5W-30

Change every 15000 km/ 12 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth LSP Ultra 5W-30

Change every 7500 km/ 6 months

DIFFERENTIAL REAR
Capacity: 1,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Check every 48 months/ 60000 km

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Change every 120000 km

TRANSAXLE AUTOMATIC 6/1
Capacity: 9,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 48 months/ 60000 km

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 100000 km

HYUNDAI (EU) EQUUS / CENTENNIAL VI

EQUUS / CENTENNIAL 4.6 V8 MPI (2010-2011)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 13,5-13,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 90000 km/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.