

# HYUNDAI (EU) GENESIS DH GENESIS 3.3 GDI V6 (2014-2016)

**ENGINE** Lambda II

Capacity: 7,3 liter (Dry fill), Capacity: 6,9 liter (Service fill), Filter capacity: 0,1 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Check every 500 km, change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

## PRODUCT RECOMMENDATION 2

**Duranza LSP 5W-30**

## PRODUCT RECOMMENDATION 3

**Armado Synth LSP Ultra 5W-30***Check every 500 km, change every 15000 km/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Severe | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Check every 500 km, change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

## PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

## PRODUCT RECOMMENDATION 2

**Duranza LSP 5W-30**

## PRODUCT RECOMMENDATION 3

**Armado Synth LSP Ultra 5W-30***Check every 500 km, change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

## PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 60000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

## PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 60000 km/ 24 months, change every 120000 km*

# HYUNDAI (EU) GENESIS DH GENESIS 3.3 GDI V6 (2014-2016)


**TRANSMISSION AUTOMATIC A8LR1 8/1**

Capacity: 10,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4036</b>     |  |          |

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Severe                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4036</b>     |  |          |

Change every 90000 km

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,7-0,8 liter

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Check every 12 months/ 30000 km

**COOLING SYSTEM**

Capacity: 8,4 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Change every 30000 km/ 24 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| First change only        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

**AIRCONDITIONING COMPRESSOR**

Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-1234yf**

Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

# HYUNDAI (EU) GENESIS DH GENESIS 3.3 GDI V6 (2014-2016)



**AIRCONDITIONING SYSTEM R-134a**  
Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*