

**HYUNDAI (EU) I10 IA I10 1.0 LPGI (2014-2017)****ENGINE** Kappa

Capacity: 3,3 liter (Dry fill), Capacity: 3 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>	<b>Armado Synth LSP Ultra 5W-30</b>

*Check every 500 km, change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>	<b>Armado Synth LSP Ultra 5W-30</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>	<b>Armado Synth LSP Ultra 5W-30</b>

*Check every 500 km, change every 15000 km/ 12 months*

USE	CLIMATE
Severe, first change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>	<b>Armado Synth LSP Ultra 5W-30</b>

*Change every 7500 km/ 6 months***TRANSAXLE MANUAL** M5EF2 5/1

Capacity: 1,9-2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Gear 1081</b>		

*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Gear 1081</b>		

*Change every 120000 km*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 20000 km, change every 40000 km/ 24 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 15000 km/ 12 months, change every 35000 km/ 24 months***COOLING SYSTEM**

Capacity: 4,8 liter (with automatic transmission), Capacity: 4,9 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 40000 km/ 48 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 210000 km/ 120 months***AIRCONDITIONING SYSTEM R-1234yf**

Capacity: 375-425 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-134a**

Capacity: 375-425 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*