HYUNDAI (EU) 110 PA 110 1.1 CRDI (2008-2010)



ENGINE D4FA Capacity: 5,5 liter (Dry fill), Capacity: 5,3 liter (Service fill)				
USE				
	Moderate			
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40			
	CLIMATE			
	Moderate			
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40			
	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40 PRODUCT RECOMMENDATION 2			

Change every 15000 km

TRANSAXLE MANUAL M5CF1 5/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

HYDRAULIC BRAKE/CLUTCH SYSTE Capacity: 0-0 liter (Between min and ma		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km

POWER STEERING Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	



COOLING SYSTEM Capacity: 5,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 20000 km, change every 55000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.