

HYUNDAI (EU) I20 GB/IB I20 1.4 MPI (2014-2020)

**ENGINE** Kappa

Capacity: 3,9 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Duranza LSP 5W-30

Check every 500 km, change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Duranza LSP 5W-30

*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC** A4CF1 4/1

Capacity: 6,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Change every 100000 km***TRANSAXLE MANUAL** M6CF1 6/1

Capacity: 1,8-1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 60000 km/ 48 months, change every 120000 km

HYUNDAI (EU) I20 GB/IB I20 1.4 MPI (2014-2020)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km/ 12 months, change every 40000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 35000 km/ 24 months

COOLING SYSTEM

Capacity: 5,6 liter (with automatic transaxle), Capacity: 5,5 liter (with manual transaxle)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 40000 km/ 48 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 100-120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-1234yf

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.