

HYUNDAI (EU) I30 FD I30 1.6 CRDI VGT DPF (94 KW) (2007-2009)

**ENGINE D4FB**

Capacity: 5,7 liter (Dry fill), Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Meganza MSP 5W-30

Change every 20000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Helar SP LL-03 0W-30		

Change every 20000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Meganza MSP 5W-30

Change every 10000 km/ 6 months

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1		
Helar SP LL-03 0W-30		

*Change every 10000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 15000 km/ 12 months, change every 95000 km/ 60 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 45000 km

HYUNDAI (EU) I30 FD I30 1.6 CRDI VGT DPF (94 KW) (2007-2009)



TRANSAXLE MANUAL 6/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 48 months/ 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 40000 km/ 48 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 6,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 210000 km/ 120 months

HYUNDAI (EU) I30 FD I30 1.6 CRDI VGT DPF (94 KW) (2007-2009)



AIRCONDITIONING COMPRESSOR

Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.