HYUNDAI (EU) I30 GDE (EU) I30 1.4 MPI (73 KW) (2015-2017)



| use Normal | | climate Moderate |
|----------------------------------|--------------------------|--------------------------|
| | | |
| Presteza MSP 5W-30 | Duranza LSP 5W-30 | Helar MSP+ 5W-40 |
| Check every 500 km, change every | 30000 km/ 12 months | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30 | Duranza LSP 5W-30 | Helar MSP+ 5W-40 |
| Check every 500 km, change every | 15000 km/ 6 months | |
| USE | | CLIMATE |
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Duranza ECO 5W-20 | | |
| Check every 500 km, change every | 15000 km/ 12 months | |
| USE | | CLIMATE |
| Severe (alternative) | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Duranza ECO 5W-20 | | |
| Check every 500 km, change every | 7500 km/ 6 months | |
| | | |
| TRANSAXLE MANUAL M6CF1 6/ | 1 | |
| Capacity: 1,8-1,9 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear 1081 | | |

Check every 60000 km/ 48 months, change every 120000 km

Severe

SP Gear 1081

PRODUCT RECOMMENDATION 1

Moderate

HYUNDAI (EU) I30 GDE (EU) I30 1.4 MPI (73 KW) (2015-2017)



| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,7-0,8 liter | | | | | |
|---|--------------------------|--------------------------|--|--|--|
| USE | | CLIMATE | | | |
| Normal | | Moderate | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 | | | |
| | | | | | |

Change every 30000 km/24 months

| COOLING SYSTEM Capacity: 5,8 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 30000 km/24 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Check every 60000 km/48 months, change every 210000 km/120 months

AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-1234yf

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.