HYUNDAI (EU) 140 VF 140 1.6 GDI (2015-2017)



ENGINE Gamma Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Duranza LSP 5W-30		
Check every 500 km, change every 30000 km/24 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Duranza LSP 5W-30		
Check every 500 km, change every 15000 km/ 12 months				

TRANSAXLE MANUAL M6CF1 6/1 Capacity: 1,6-1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
Check every 48 months/ 60000 km	
HOE	OLIMATE

USE	CLIMATE			
Severe	Moderate			
PRODUCT RECOMMENDATION 1				
SP Gear 1081				

Check every 60000 km/ 48 months, change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTI Capacity: 0,7-0,8 liter	ΞM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 30000 km/ 24 months	'	

HYUNDAI (EU) 140 VF 140 1.6 GDI (2015-2017)



COOLING SYSTEM Capacity: 6,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 30000 km/24 month	s	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 60000 km/ 48 months,	change every 210000 km/ 120 months	

AIRCONDITIONING COMPRESSOR Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.