

HYUNDAI (EU) I40 VF I40 1.7 CRDI (104 KW) (2015-2017)

**ENGINE D4FD**

Capacity: 5,7 liter (Dry fill), Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Asyntho 5W-30	Bi-Turbo 15W-40

Check every 500 km, change every 30000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Asyntho 5W-30	Bi-Turbo 15W-40

*Check every 500 km, change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC A6MF2 6/1**

Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4036	

*Check every 60000 km/ 48 months, change every 90000 km***TRANSAXLE MANUAL M6GF2 6/1**

Capacity: 1,8-2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 1081	

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 1081	

Check every 60000 km/ 48 months, change every 120000 km

HYUNDAI (EU) I40 VF I40 1.7 CRDI (104 KW) (2015-2017)



TRANSAXLE SEMI-AUTOMATIC D7UF1 7/1

Capacity: 1,9-2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 60000 km/ 48 months, change every 90000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 30000 km/ 24 months*

COOLING SYSTEM

Capacity: 6,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 30000 km/ 24 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Check every 60000 km/ 48 months, change every 210000 km/ 120 months*

AIRCONDITIONING SYSTEM R-134a

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.