

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (100 KW) (2007-2009)



ENGINE A2.5
Capacity: 7,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

Change every 15000 km/ 12 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

Change every 7500 km/ 6 months

DIFFERENTIAL REAR
Capacity: 1,8-2,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Check every 24 months/ 30000 km

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Change every 90000 km

TRANSMISSION AUTOMATIC A5SR1 5/1
Capacity: 10 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 15000 km/ 12 months, change every 90000 km/ 72 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 40000 km

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (100 KW) (2007-2009)



TRANSMISSION MANUAL 6/1

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Check every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Change every 100000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 15000 km/ 12 months*

POWER STEERING

Capacity: 0,9-1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 15000 km/ 12 months*

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (100 KW) (2007-2009)

**COOLING SYSTEM**

Capacity: 10-13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 40000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 100000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.