HYUNDAI (EU) IX55 / VERACRUZ EN IX55 / VERACRUZ 3.0 CRDI VGT (2007-2011)



ENGINE Capacity: 7,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40
Change every 20000 km/ 12 months	s	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40
Change every 10000 km/6 months		

TRANSAXLE AUTOMATIC F21 6/1 Capacity: 7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Check every 60000 km/ 36 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Check every 60000 km/ 36 months, change	e every 90000 km		

HYDRAULIC BRAKE SYSTEM Capacity: 0,7-0,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	

HYUNDAI (EU) IX55 / VERACRUZ EN IX55 / VERACRUZ 3.0 CRDI VGT (2007-2011)



POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 20000 km/ 12 months	

COOLING SYSTEM Capacity: 9,8-11,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 40000 km/48 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 100000 km/60 months

AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3 (Front), Capacity: 200-220 CM3 (Front and rear)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 675-725 grams (Front), Capacity: 875-925 grams (Front and rear)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.