

# HYUNDAI (EU) SANTA FE CM SANTA FE 2.2 CRDI (2006-2010)

**ENGINE D4EB**

Capacity: 5,9 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC A5HF1 5/1**

Capacity: 7,8 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 30000 km/ 24 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL M5HF2 5/1**

Capacity: 1,85 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Check every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Change every 100000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 15000 km/ 12 months, change every 24 months*

# HYUNDAI (EU) SANTA FE CM SANTA FE 2.2

## CRDI (2006-2010)



### POWER STEERING

Capacity: 0,9 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

### GREASE POINTS/NIPPLES

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

### COOLING SYSTEM

Capacity: 8,4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12***Change every 45000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.