

HYUNDAI (EU) SONATA / I45 YF SONATA / I45 2.4 MPI HYBRID (2014-2015)

**ENGINE** Theta II

Capacity: 6,1 liter (Dry fill with red dipstick), Capacity: 5,5 liter (Dry fill with yellow dipstick), Capacity: 5 liter (Service fill with red dipstick), Capacity: 4,6 liter (Service fill with yellow dipstick), Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Emperol 10W-40	Armado Synth LSP Ultra 5W-30

Check every 500 km, change every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Emperol 10W-40	Armado Synth LSP Ultra 5W-30

Check every 500 km, change every 7500 km/ 6 months

TRANSAXLE AUTOMATIC A6MF2H 6/1

Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 48 months/ 60000 km

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 60000 km/ 48 months, change every 90000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

HYUNDAI (EU) SONATA / I45 YF SONATA / I45 2.4 MPI HYBRID (2014-2015)



COOLING SYSTEM

Capacity: 6,6-6,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 115-135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.