## **HYUNDAI (EU) SONATA Y2 SONATA 2.01**

(1988-1992)



	4 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 10000 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Change every 5000 km/ 3 months		
USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 5000 km/ 3 months		

TRANSAXLE AUTOMATIC 4/1 Capacity: 5,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 20000 km, change every 40000 km/24 months

TRANSAXLE MANUAL 5/1 Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	SP Gear 1071
Check every 20000 km, change ev	ery 40000 km/ 24 months	

## **HYUNDAI (EU) SONATA Y2 SONATA 2.01**

(1988-1992)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 40000 km, change every 80000 km/24 months

POWER STEERING Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 20000 km, change every	40000 km/ 24 months	

GREASE POINTS/NIPPLES BALL JOINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 20000 km/ 12 months	<u>'</u>	

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 20000 km/ 12 months		

COOLING SYSTEM Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 50000 km/ 24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.