## JAGUAR (EU) F-TYPE X152 F-TYPE 3.0 V6 (250 KW) (2015-2016)



ENGINE AJ126 Capacity: 8,75 liter (Dry fill), Capacity: 7,25	iliter (Service fill)	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 26000 km/ 12 months		

## **DIFFERENTIAL REAR** Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC ZF 8HP70 Capacity: 8,5 liter	) 8/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		
Change every 48000 km		

TRANSMISSION MANUAL 6/1 Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2072	
USE	CLIMATE
use Severe	climate Moderate
Severe	

## JAGUAR (EU) F-TYPE X152 F-TYPE 3.0 V6 (250 KW) (2015-2016)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 36 months	

HYDRAULIC BRAKE SYSTEM CARBON		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid Racing		

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

COOLING SYSTEM Capacity: 13,5 liter (Dry fill), Capaci	ity: 9,6 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 260000 km/ 120 mod	nths	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.