

JAGUAR (EU) F-TYPE X152 F-TYPE S 5.0 V8 (364 KW) (2013-2014)



MOTOR AJ133

Kapacitet: 7,25 liter (Servicepåfyldning), Kapacitet: 8,9 liter (Tør efterfyld), Filterkapacitet: 0,5 liter

ANVEND

Normal (alternativ)

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Skift alle 26000 km/ 12 måneder

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 26000 km/ 12 måneder

DIFFERENTIALE BAG ELEKTRONISK MOMENTSTYRING (ETM)

Kapacitet: 1,2-1,22 liter (Servicepåfyldning), Kapacitet: 1,24-1,26 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear LS 1015

GEAR AUTOMATISK ZF 8HP70 8/1

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2034

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2034

Skift alle 48000 km

JAGUAR (EU) F-TYPE X152 F-TYPE S 5.0 V8 (364 KW) (2013-2014)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 36 måneder

HYDRAULISK BREMSESYSTEM KULSTOF

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid Racing

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

KØLESYSTEM

Kapacitet: 9,2 liter (Servicepåfyldning), Kapacitet: 12,32 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 260000 km/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.