

JAGUAR (EU) XF X250 XF 3.0D V6 S (202 KW) DPF (2009-2012)



MOTOR

Kapacitet: 6,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Elvado LSP 5W-30

Skift alle 24000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

GEAR AUTOMATISK ZF 6HP26 6/1

Kapacitet: 10,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 24000 km/ 12 måneder, skift alle 240000 km/ 120 måneder

HYDRAULISK BREMSESYSTEM ABS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 24000 km/ 12 måneder, skift alle 36 måneder

SERVOSTYRING

Kapacitet: 1,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Kontroller alle 24000 km/ 12 måneder

JAGUAR (EU) XF X250 XF 3.0D V6 S (202 KW) DPF (2009-2012)



KØLESYSTEM

Kapacitet: 12,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 24000 km/ 12 måneder, skift alle 240000 km/ 120 måneder

AIRCONDITION

Kapacitet: 750 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 110 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.