

JAGUAR (EU) F-TYPE X152 F-TYPE 3.0 V6 (250 KW) (2015-2016)

**ENGINE AJ126**

Capacity: 8,75 liter (Dry fill), Capacity: 7,25 liter (Service fill)

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20***Change every 26000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC ZF 8HP70 8/1

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2034****USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2034***Change every 48000 km***TRANSMISSION MANUAL 6/1**

Capacity: 1,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2072****USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2072***Change every 240000 km/ 120 months*

JAGUAR (EU) F-TYPE X152 F-TYPE 3.0 V6 (250 KW) (2015-2016)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 36 months*

HYDRAULIC BRAKE SYSTEM CARBON

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid Racing

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

COOLING SYSTEM

Capacity: 13,5 liter (Dry fill), Capacity: 9,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 260000 km/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.