JAGUAR (EU) F-TYPE X152 F-TYPE R 5.0 V8 (406 KW) (2014-2014)



| ENGINE AJ133 Capacity: 8,9 liter (Dry fill), Capacity: 6,5 lit | er (Service fill) | |
|--|-------------------|----------|
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Duranza ECO 5W-20 | | |
| Change every 26000 km/ 12 months | | |
| USE | | CLIMATE |
| Flexible (max) | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Presteza MSP 0W-20 | | |
| Change every 26000 km/ 12 months | | |

| DIFFERENTIAL REAR ELECTRONIC TORQUE MANAGED (ETM Capacity: 1,24-1,26 liter (Dry fill), Capacity: 1,2-1,22 liter (Service fill) | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear LS 1015 | | |
| | | |

| TRANSMISSION AUTOMATIC ZF 8HP70 8/1 Capacity: 8,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2034 | | |
| | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2034 | | |
| Change every 48000 km | | |

| HYDRAULIC BRAKE SYSTEM | |
|---------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| <u>0</u> | |

Change every 36 months

JAGUAR (EU) F-TYPE X152 F-TYPE R 5.0 V8 (406 KW) (2014-2014)



| IYDRAULIC BRAKE SYSTEM CARBON | | |
|-------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid Racing | | |

| POWER STEERING | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |

| COOLING SYSTEM Capacity: 12,32 liter (Dry fill), Capacity: 9,2 liter (Service fill) | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Change every 260000 km/ 120 mol | nths | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.