

JAGUAR (EU) F-TYPE X152 F-TYPE S 5.0 V8 (364 KW) (2013-2014)

**ENGINE** AJ133

Capacity: 8,9 liter (Dry fill), Capacity: 7,25 liter (Service fill), Filter capacity: 0,5 liter

USE

Normal (alternative)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20*Change every 26000 km/ 12 months*

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 26000 km/ 12 months***DIFFERENTIAL REAR ELECTRONIC TORQUE MANAGED (ETM)**

Capacity: 1,24-1,26 liter (Dry fill), Capacity: 1,2-1,22 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015**TRANSMISSION AUTOMATIC** ZF 8HP70 8/1

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034*Change every 48000 km*

JAGUAR (EU) F-TYPE X152 F-TYPE S 5.0 V8 (364 KW) (2013-2014)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 36 months

HYDRAULIC BRAKE SYSTEM CARBON

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid Racing		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 12,32 liter (Dry fill), Capacity: 9,2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 260000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.