

JAGUAR (EU) XF X250 XF 2.2D TD4 (140 KW) (2012-2015)

**ENGINE**

Capacity: 6,5 liter (Dry fill), Capacity: 5,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 26000 km/ 12 months*

USE	CLIMATE
Severe, high sulfur fuel	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 13000 km***DIFFERENTIAL REAR**

Capacity: 0,85 liter (Dry fill), Capacity: 0,82 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90**TRANSMISSION AUTOMATIC ZF 8HP70 8/1**

Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034*Change every 48000 km*

JAGUAR (EU) XF X250 XF 2.2D TD4 (140 KW) (2012-2015)



HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Change every 36 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

COOLING SYSTEM

Capacity: 11,56 liter (Dry fill), Capacity: 8,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

Change every 260000 km/ 120 months

AIRCONDITIONING

Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.