JAGUAR (EU) XJ X350, X358 XJ6 3.0 (2003-2006)



ENGINE Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Helar 0W-40	Emperol 5W-40
Change every 16000 km/ 12 months	;	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Duranza LSP 5W-30
Change every 16000 km/ 12 months		

DIFFERENTIAL REAR Capacity: 1,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Check every 16000 km/ 12 months	'

TRANSMISSION AUTOMATIC ZF 6HP26 6/1 Capacity: 9,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Check every 16000 km/ 12 months			

HYDRAULIC BRAKE SYSTEM ABS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 16000 km/ 12 months, cha	nge every 24 months	·

JAGUAR (EU) XJ X350, X358 XJ6 3.0 (2003-2006)



POWER STEERING Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 16000 km/ 12 months		,

COOLING SYSTEM Capacity: 10,25-11,05 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF	

Check every 16000 km/12 months, change every 240000 km/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.