JAGUAR (EU) XJ X308 XJ8 4.0 (2001-2003)



JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 16000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 16000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 6 months		
DIFFERENTIAL REAR Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 16000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		

JAGUAR (EU) XJ X308 XJ8 4.0 (2001-2003)



TRANSMISSION AUTOMATIC ZF 5/1 Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 16000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 6 months		

HYDRAULIC BRAKE SYSTEM ABS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 16000 km/ 12 months, change every 24 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

032		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4		
Change every 6 months	·	·

HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 16000 km/ 12 months		
USE		CLIMATE

USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4			
Check every 6 months	-	'	

JAGUAR (EU) XJ X308 XJ8 4.0 (2001-2003)



POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Dexron II-D	
Check every 16000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Dexron II-D	
Check every 6 months		

COOLING SYSTEM Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

Check every 16000 km/ 12 months, change every 240000 km/ 60 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 6 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.