

JAGUAR (EU) XJS XJ27 XJS 4.0 (1995-1997)**ENGINE AJ-16**

Capacity: 8 liter, Filter capacity: 0,55 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 12000 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Emperol 5W-50	Emperol Racing 10W-60

Change every 12000 km/ 6 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

*Change every 12000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

*Check every 12000 km/ 6 months***TRANSMISSION AUTOMATIC ZF 4/1**

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Change every 48000 km/ 24 months

JAGUAR (EU) XJS XJ27 XJS 4.0 (1995-1997)
TRANSMISSION MANUAL Getrag 5/1
 Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 12000 km/ 6 months, change every 48000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 12000 km/ 6 months, change every 24 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 12000 km/ 6 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 12000 km/ 6 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 24000 km/ 12 months

JAGUAR (EU) XJS XJ27 XJS 4.0 (1995-1997)**COOLING SYSTEM**

Capacity: 9,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 48000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.