JAGUAR (EU) XK X150 XK 5.0 V8 (2014-2015)



ENGINE Capacity: 7,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-20	
Change every 2/000 km/ 12 months	

Change every 24000 km/ 12 months

DIFFERENTIAL REAR Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

TRANSMISSION AUTOMATIC ZF 6HP28 Capacity: 10 liter (Dry fill), Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

HYDRAULIC BRAKE SYSTEM ABS Capacity: 0-0 liter (Between min and max.)	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Drauliquid-LV Super DOT 4	

Check every 24000 km/ 12 months, change every 24 months

POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 24000 km/ 12 months	

JAGUAR (EU) XK X150 XK 5.0 V8 (2014-2015)



COOLING SYSTEM Capacity: 10,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 24000 km/ 12 months, change every 240000 km/ 120 months

AIRCONDITIONING

Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.