

KIA (EU) OPTIMA TF OPTIMA 2.4 MPI (2012-2016)



MOTOR Theta II 2.4

Kapacitet: 4,8 liter (Servicepåfyldning), Kapacitet: 5,8 liter (Tør efterfyld), Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Duranza ECO 5W-20	Duranza LSP 5W-30	

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Specialsynth MSP 5W-40

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Alternativ, svær	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Specialsynth MSP 5W-40

Kontroller alle 500 km, skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Foretrukken, alvorlig	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Duranza ECO 5W-20	Duranza LSP 5W-30	

Kontroller alle 500 km, skift alle 7500 km/ 6 måneder

TRANSAXSEL AUTOMATISK A6MF1 6/1

Kapacitet: 7,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

Skift alle 90000 km

KIA (EU) OPTIMA TF OPTIMA 2.4 MPI (2012-2016)



TRANSAKSEL MANUEL M6GF2 6/1

Kapacitet: 1,8-1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 48 måneder/ 60000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 60000 km/ 48 måneder, skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 15000 km/ 12 måneder

KIA (EU) OPTIMA TF OPTIMA 2.4 MPI (2012-2016)



KØLESYSTEM

Kapacitet: 6,5-6,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 30000 km/ 24 måneder, skift alle 30000 km/ 24 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder

AIRCONDITION

Kapacitet: 525-575 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 90-110 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.