

KIA (EU) PICANTO SA PICANTO 1.0 (2004-2007)



MOTOR

Kapacitet: 3 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

Skift alle 15000 km/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Skift alle 15000 km/ 12 måneder

ANVEND		KLIMA
Krævende		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

Skift alle 7500 km/ 6 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Skift alle 7500 km/ 6 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 15000 km/ 12 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

KIA (EU) PICANTO SA PICANTO 1.0 (2004-2007)



SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 3,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 15000 km/ 12 måneder, skift alle 90000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.