KIA (EU) CEE'D ED CEE'D 2.0 CVVT (2007-2009)



ENGINE G4GC Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Specialsynth MSP 5W-40	Helar 0W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Specialsynth MSP 5W-40	Helar 0W-40
Change every 7500 km/ 6 months	·	·

TRANSAXLE AUTOMATIC A4CF2 4/1 Capacity: 6,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 15000 km/ 12 months, change	ge every 90000 km/ 72 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		

Check every 15000 km/ 12 months, change every 45000 km

TRANSAXLE MANUAL M5CF2 5. Capacity: 2 liter	/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 15000 km/ 12 months	, change every 100000 km	

SP Matic 4026

KIA (EU) CEE'D ED CEE'D 2.0 CVVT (2007-2009)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,7-0,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	

Check every 15000 km/12 months, change every 30000 km/24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 6,2-6,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 15000 km/ 12 months	, change every 45000 km	

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 15000 km/12 months, change every 90000 km/60 months

AIRCONDITIONING COMPRESSOR Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.