## KIA (EU) CERATO / SPECTRA LD CERATO / SPECTRA 1.5 CRDI (2005-2007)



ENGINE D4FA Capacity: 5,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Asyntho 5W-30 Dieselfleet CD+ 15W-40		Bi-Turbo 15W-40	
Change every 15000 km/ 12 month	s	·	
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Asyntho 5W-30	Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40	
Change every 7500 km/ 6 months	,		

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Syngear 75W-90

Check every	15000 k	km/12	months	change	everv	90000 kr	n

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,7-0,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Check every 15000 km/ 12 months, ch	ange every 30000 km/24 months		

**SP Gear 5015** 

## KIA (EU) CERATO / SPECTRA LD CERATO / SPECTRA 1.5 CRDI (2005-2007)



POWER STEERING Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 24 months/ 30000 km	•	

COOLING SYSTEM Capacity: 8,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 15000 km/12 months, change every 45000 km/24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 15000 km/ 12 months, change every 90000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.