

**KIA (EU) RIO UB RIO 1.4 CVVT (2011-2014)****ENGINE y-1.4**

Capacity: 3,7 liter (Dry fill), Capacity: 3,3 liter (Service fill), Filter capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Specialsynth MSP 5W-40</b>	<b>Helar 0W-40</b>

*Check every 500 km, change every 15000 km/ 12 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Specialsynth MSP 5W-40</b>	<b>Helar 0W-40</b>

*Check every 500 km, change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC A4CF1 4/1**

Capacity: 6,8 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 60000 km, change every 100000 km*

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 60000 km***TRANSAXLE MANUAL M6CF1 6/1**

Capacity: 1,8-1,9 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 60000 km, change every 120000 km*

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 60000 km*

**KIA (EU) RIO UB RIO 1.4 CVVT (2011-2014)****HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,7-0,8 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 12 months***COOLING SYSTEM**

Capacity: 5,3 liter, Capacity: 5,5 liter (with automatic transaxle)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 30000 km/ 24 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 60000 km/ 48 months, change every 210000 km/ 120 months***AIRCONDITIONING**

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING COMPRESSOR**

Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*