KIA (EU) RIO UB RIO 1.6 CVVT (2011-2014)



ENGINE y-1.6 GDI Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Duranza LSP 5W-30	Specialsynth MSP 5W-40		
Check every 500 km, change every 15000 km/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Duranza LSP 5W-30	Specialsynth MSP 5W-40		
Check every 500 km, change every 7500 km/ 6 months				

TRANSAXLE AUTOMATIC A6GF1 6/1 Capacity: 7,3 liter			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 60000 km, change every 100000 km			
USE		CLIMATE	
Filled for life		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

TRANSAXLE MANUAL M6CF1 6. Capacity: 1,8-1,9 liter	/1	
use Severe		climate Moderate
SP Gear 5015	Syngear 75W-90	
Check every 60000 km, change ev	ery 120000 km	·
USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 60000 km		•

Check every 60000 km

KIA (EU) RIO UB RIO 1.6 CVVT (2011-2014)



HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,7-0,8 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		

Check every 12 months

COOLING SYSTEM Capacity: 5 liter, Capacity: 5,2 liter (with automatic transaxle)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15+	Coolant SP 12			
Change every 30000 km/ 24 months				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15+	Coolant SP 12			

Check every 60000 km/48 months, change every 210000 km/120 months

AIRCONDITIONING

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.