

# KIA (EU) SPORTAGE AL / KM SPORTAGE

## 2.0 CRDI VGT 2WD DPF (2008-2010)



**ENGINE** D4EA  
Capacity: 5,9 liter

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 3

**Meganza MSP 5W-30**

*Change every 20000 km/ 12 months*

**USE**  
Normal

**CLIMATE**  
Cold

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 0W-30**

*Change every 20000 km/ 12 months*

**USE**  
Severe

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 3

**Meganza MSP 5W-30**

*Change every 10000 km/ 6 months*

**USE**  
Severe

**CLIMATE**  
Cold

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 0W-30**

*Change every 10000 km/ 6 months*

**TRANSAXLE AUTOMATIC 4/1**  
Capacity: 8,5 liter

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

*Check every 20000 km/ 12 months, change every 120000 km/ 72 months*

**USE**  
Severe

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

*Check every 20000 km/ 12 months, change every 40000 km*

# KIA (EU) SPORTAGE AL / KM SPORTAGE

## 2.0 CRDI VGT 2WD DPF (2008-2010)



### TRANSAXLE MANUAL M6 6/1

Capacity: 1,9 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Syngear 75W-90</b>    |          |

Check every 20000 km/ 12 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Syngear 75W-90</b>    |          |

Check every 20000 km/ 12 months, change every 100000 km

### HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Check every 20000 km, change every 40000 km/ 24 months

### POWER STEERING

Capacity: 0,9 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

Check every 24 months/ 30000 km

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# KIA (EU) SPORTAGE AL / KM SPORTAGE

## 2.0 CRDI VGT 2WD DPF (2008-2010)

**COOLING SYSTEM**

Capacity: 8,7 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Check every 20000 km, change every 40000 km/ 24 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| First change only        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*