PRODUCT RECOMMENDATION

KIA (EU) SPORTAGE SL (ROW) SPORTAGE 1.6 GDI (2010-2012)

ENGINE y-1.6 GDI
Capacity: 4 liter (Dry fill, 2011-07-29 onwards), Capacity: 3,7 liter (Dry fill, upto 2011-07-28), Capacity: 3,6 liter (Service fill, 2011-07-29 onwards), Capacity: 3,3 liter (Service fill, upto 2011-07-28), Filter capacity: 0,3 liter

USE		CLIMATE
Severe (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		

Check every 500 km, change every 15000 km/ 6 months

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	**Asyntho 5W-30**	

Check every 500 km, change every 15000 km

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		

Check every 500 km, change every 30000 km/ 24 months

USE		CLIMATE
Severe (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	**Asyntho 5W-30**	

Check every 500 km, change every 7500 km

TRANSAXLE MANUAL M6CF1 6/1
Capacity: 1,8-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Syngear 75W-90**	

Check every 48 months/ 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Syngear 75W-90**	

Check every 60000 km/ 48 months, change every 120000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KIA (EU) SPORTAGE SL (ROW) SPORTAGE 1.6 GDI (2010-2012)

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 30000 km/ 24 months

POWER STEERING
Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months

COOLING SYSTEM
Capacity: 6,5-6,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15+	**Coolant SP 12**	

Check every 30000 km/ 24 months, change every 30000 km/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15+	**Coolant SP 12**	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR
Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a
Capacity: 485-535 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367