

KIA (EU) SPORTAGE SL (ROW) SPORTAGE 2.0 CVVT (2010-2012)

**ENGINE**

Capacity: 4,7 liter (Dry fill), Capacity: 6,4-6,8 liter (Dry fill with oil level sensor), Capacity: 4,1 liter (Service fill), Capacity: 5,8-6 liter (Service fill with oil level sensor), Filter capacity: 0,3-0,4 liter

USE	CLIMATE
Severe (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

Check every 500 km, change every 15000 km/ 6 months

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

Check every 500 km, change every 15000 km

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

Check every 500 km, change every 30000 km/ 24 months

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

Check every 500 km, change every 7500 km

TRANSAXLE AUTOMATIC A6MF1 6/1

Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 90000 km

KIA (EU) SPORTAGE SL (ROW) SPORTAGE 2.0 CVVT (2010-2012)



TRANSAXLE MANUAL M5GF1 5/1

Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 60000 km/ 48 months, change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

POWER STEERING

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months

KIA (EU) SPORTAGE SL (ROW) SPORTAGE 2.0 CVVT (2010-2012)

**COOLING SYSTEM**

Capacity: 6,5-6,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 30000 km/ 24 months, change every 30000 km/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 485-535 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.