## **LANCIA PRISMA PRISMA 1600** (1983-1987)



|                          | CLIMATE  |
|--------------------------|----------|
|                          | Moderate |
| PRODUCT RECOMMENDATION 2 |          |
| Bi-Turbo 15W-40          |          |
|                          |          |

Change every 10000 km/6 months

| TRANSAXLE MANUAL 5/1 Capacity: 3 liter |          |
|--|----------|
| USE                                    | CLIMATE  |
| Normal                                 | Moderate |
| PRODUCT RECOMMENDATION 1               |          |
| Gearlube GL-4 80W-90                   |          |
| 01 1 400001 10 11 1 400001             | 104      |

Check every 10000 km/6 months, change every 40000 km/24 months

| HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter |     |         |
|--|-----|---------|
| USE  | CLI | MATE    |
| Normal                                     | Mo  | oderate |
| PRODUCT RECOMMENDATION 1                   |     |         |
| Drauliquid DOT 3                           |     |         |
| Chairman arrain 40000 km²/40 magintha      |     |         |

Change every 40000 km/ 48 months

| GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS |  |          |
|--|--|----------|
| USE                                      |  | CLIMATE  |
| Normal                                   |  | Moderate |
| PRODUCT RECOMMENDATION 1                 |  |          |
| MoS2 Grease EP 2                         |  |          |
|  |  |          |

| COOLING SYSTEM Capacity: 6,3 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Coolant -38 Organic NF             |          |
| Change every 60000 km/24 months    | ·        |

## PRODUCT RECOMMENDATION

## LANCIA PRISMA PRISMA 1600 (1983-1987)



## **STEERING GEAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.