LANCIA YPSILON 312 YPSILON 0.9 TWINAIR TURBO (59 KW) (2014-2018)



ENGINE 312A5000 Capacity: 3,3 liter (Service fill), Filter capacity: 0,5 liter		
USE	CLIMATE	
Preferred by OEM	Moderate	
PRODUCT RECOMMENDATION 1		
Avanza MSP 0W-30		
Change every 15000 km/ 12 months		
USE	CLIMATE	
Flexible (max)	Moderate	
PRODUCT RECOMMENDATION 1		
Avanza MSP 0W-30		
Change every 30000 km/ 24 months		
USE	CLIMATE	
City usage	Moderate	
PRODUCT RECOMMENDATION 1		
Avanza MSP 0W-30		
Change every 12 months		

TRANSAXLE MANUAL 5/1 Capacity: 1,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 90000 km/ 72 months	· · · · · · · · · · · · · · · · · · ·	-

TRANSAXLE SEMI-AUTOMATIC Capacity: 1,55 liter	5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 90000 km/ 72 months		

LANCIA YPSILON 312 YPSILON 0.9 TWINAIR TURBO (59 KW) (2014-2018)



HYDRAULIC ACTUATION GEARBOX Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		
Check every 24 months/ 30000 km		
USE		CLIMATE
Cold climate		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		
Check every 15000 km/ 12 months		

HYDRAULIC BRAKE SYSTEM Capacity: 0,55 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 30000 km/ 24 months			

Change every 30000 km/24 months

COOLING SYSTEM Capacity: 5,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 15000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.