

LAND ROVER (EU) DEFENDER L316

DEFENDER 110 TDI (1990-1994)

**ENGINE**

Capacity: 6,65 liter (Total), Filter capacity: 0,85 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Bi-Turbo 15W-40***Change every 10000 km/ 6 months***DIFFERENTIAL FRONT**

Capacity: 1,7 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Gearlube GL-5 80W-90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube RPC 75W-80****PRODUCT RECOMMENDATION 3****SP Gear 1071***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***DIFFERENTIAL REAR Salisbury**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Gearlube GL-5 80W-90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube RPC 75W-80****PRODUCT RECOMMENDATION 3****SP Gear 1071***Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

LAND ROVER (EU) DEFENDER L316

DEFENDER 110 TDI (1990-1994)

**TRANSFERBOX LT230T**

Capacity: 2,8 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION MANUAL LT77 5/1

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 30000 km/ 18 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

LAND ROVER (EU) DEFENDER L316

DEFENDER 110 TDI (1990-1994)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES PROPELLER SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 10000 km/ 6 months

GREASE POINTS/NIPPLES PROPELLER SHAFT SLIDING JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 40000 km/ 24 months

GREASE POINTS/NIPPLES SWIVEL PIN HOUSINGS

Capacity: 0,35 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

LAND ROVER (EU) DEFENDER L316

DEFENDER 110 TDI (1990-1994)



COOLING SYSTEM

Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 40000 km/ 48 months

STEERING BOX

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

Check every 20000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.