

LAND ROVER (EU) RANGE ROVER L322/LM

RANGE ROVER V8 5.0 SC (2009-2012)

**ENGINE 508PS - AJV8 5.0 SC**

Capacity: 9,65 liter (Dry fill), Capacity: 8 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 24000 km/ 12 months***DIFFERENTIAL FRONT**

Capacity: 0,75 liter, Capacity: 0,8 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Check every 48000 km/ 24 months, change every 240000 km/ 120 months***DIFFERENTIAL REAR**

Capacity: 1,14 liter, Capacity: 1,2 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Change every 120000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,55 liter, Capacity: 1,6 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear LS 1015***Change every 120000 km/ 12 months***TRANSFERBOX**

Capacity: 1,5 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2072***Change every 120000 km/ 60 months*

LAND ROVER (EU) RANGE ROVER L322/LM

RANGE ROVER V8 5.0 SC (2009-2012)

**TRANSMISSION AUTOMATIC** ZF 6HP26 6/1

Capacity: 9,5 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

*Change every 36 months***POWER STEERING**

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 19,8 liter (with 2 zone airconditioning system), Capacity: 20,5 liter (with 4 zone airconditioning system)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

*Check every 48000 km/ 24 months, change every 240000 km/ 120 months***AIRCONDITIONING COMPRESSOR**

Capacity: 110 CM3 (with 2 zone airconditioning system), Capacity: 200 CM3 (with 4 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 750 grams (with 2 zone airconditioning system), Capacity: 930 grams (with 4 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.