

LEXUS (EU) IS XE20 IS 220D (2008-2013)



MOTOR 2AD-FHV

Kapacitet: 6 liter (Servicepåfyldning), Kapacitet: 6,7 liter (Tør efterfyld), Filterkapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Skift alle 7500 km/ 6 måneder

DIFFERENTIALE BAG F21FS

Kapacitet: 1,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

Skift alle 30000 km/ 48 måneder

GEAR MANUEL RA63 6/1

Kapacitet: 1,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Skift alle 60000 km/ 48 måneder



HYDRAULISK BREMSESYSTEM ABS

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Drauliquid-LV Super DOT 4	PRODUKTANBEFALING 2 Drauliquid-S DOT 4	PRODUKTANBEFALING 3 Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 8,9 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 14+		

Kontroller alle 30000 km, skift alle 90000 km

ANVEND Første skift kun		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 14+		

Kontroller alle 30000 km, skift alle 150000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.