

LEXUS (EU) IS XE20 IS F (2012-2013)



MOTOR 2UR-GSE

Kapacitet: 9,3 liter (Servicepåfyldning), Kapacitet: 10,5 liter (Tør efterfyld), Filterkapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Xedoz FE 5W-30

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Xedoz FE 5W-30

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 7500 km/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 1,3-1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Skift alle 30000 km/ 48 måneder

GEAR AUTOMATISK AA80E 8/1

Kapacitet: 3,7 liter (Servicepåfyldning), Kapacitet: 10,5 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 36 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 36 måneder, skift alle 72 måneder

LEXUS (EU) IS XE20 IS F (2012-2013)



HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 11,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Skift alle 24 måneder

AIRCONDITION

Kapacitet: 400-500 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.