

LEXUS (EU) RX L1 RX 450H 2WD (2009-2012)



MOTOR 2GR-FXE

Kapacitet: 6,1 liter, Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30

Skift alle 7500 km/ 6 måneder

TRANAKSEL HYBRIDSYSTEM P313 1/1

Kapacitet: 4,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

Kontroller alle 60000 km/ 36 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Matic 4036		

Kontroller alle 45000 km/ 36 måneder, skift alle 90000 km/ 72 måneder

HYDRAULISK BREMSESYSTEM ABS

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

LEXUS (EU) RX L1 RX 450H 2WD (2009-2012)



KØLESYSTEM

Kapacitet: 11,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 90000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 150000 km

KØLESYSTEM INVERTER

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 90000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km, skift alle 240000 km

AIRCONDITION

Kapacitet: 550-650 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 120-135 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.