

LEXUS (USA / CAN) GS S160 GS 430 (USA) (2004-2005)



MOTOR 3UZ-FE

Kapacitet: 5,2 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 mil/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 1,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Kontroller alle 15000 mil/ 18 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 15000 mil/ 18 måneder

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 15000 mil/ 18 måneder

GEAR AUTOMATISK A650E 5/1

Kapacitet: 1,8 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 30000 mil/ 36 måneder

LEXUS (USA / CAN) GS S160 GS 430 (USA) (2004-2005)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 15000 mil/ 18 måneder, skift alle 30000 mil/ 36 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Kontroller alle 15000 mil/ 18 måneder

KØLESYSTEM

Kapacitet: 9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 15000 mil/ 18 måneder, skift alle 50000 mil/ 60 måneder

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 15000 mil/ 18 måneder, skift alle 100000 mil/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.