

# LEXUS (USA / CAN) LS XF30 LS 430 (USA) (2004-2005)



## MOTOR 3UZ-FE

Kapacitet: 5,1 liter (Servicepåfyldning), Filterkapacitet: 0,6 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2  |  |
|--------------------------|----------------------|--|
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b> |  |

Skift alle 5000 mil/ 6 måneder

## DIFFERENTIALE BAG

Kapacitet: 1,35 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         |  |  |
|-----------------------------|--|--|
| <b>Gearlube GL-5 80W-90</b> |  |  |

Kontroller alle 15000 mil/ 18 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2        | PRODUKTANBEFALING 3 |
|---------------------|----------------------------|---------------------|
| <b>SP Gear 5015</b> | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b> |

Kontroller alle 15000 mil/ 18 måneder

## DIFFERENTIALE BAG MED OLIEINFORMATIONSETIKET

Kapacitet: 1,35 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3   |
|---------------------|---------------------------|-----------------------|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b> |

Kontroller alle 15000 mil/ 18 måneder

# LEXUS (USA / CAN) LS XF30 LS 430 (USA) (2004-2005)



## GEAR AUTOMATISK A761E 6/1

Kapacitet: 2,4 liter (Servicepåfyldning), Kapacitet: 8,5 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 4036</b> |  |  |

Kontroller alle 30000 mil/ 36 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 4036</b> |  |  |

Kontroller alle 30000 mil/ 36 måneder, skift alle 60000 mil/ 72 måneder

## HYDRAULISK BREMSESYSTEM ABS

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Drauliquid DOT 3</b> |  |  |

Kontroller alle 5000 mil/ 6 måneder, skift alle 30000 mil/ 36 måneder

## SERVOSTYRING

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3    |
|----------------------|---------------------|------------------------|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  | <b>ATF Dexron II-D</b> |

Kontroller alle 5000 mil/ 6 måneder

## KØLESYSTEM

Kapacitet: 9,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1   |  |  |
|-----------------------|--|--|
| <b>Coolant SP 14+</b> |  |  |

Kontroller alle 15000 mil/ 18 måneder, skift alle 50000 mil/ 60 måneder

| ANVEND           | KLIMA   |
|------------------|---------|
| Første skift kun | Moderat |

| PRODUKTANBEFALING 1   |  |  |
|-----------------------|--|--|
| <b>Coolant SP 14+</b> |  |  |

Kontroller alle 15000 mil/ 18 måneder, skift alle 100000 mil/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

PRODUKTANBEFALING

# LEXUS (USA / CAN) LS XF30 LS 430 (USA) (2004-2005)



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*