

# LEXUS (USA / CAN) SC Z40 SC 430 (USA) (2003-2003)



## MOTOR 3UZ-FE

Kapacitet: 5,2 liter (Servicepåfyldning), Filterkapacitet: 0,6 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2  |
|--------------------------|----------------------|
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b> |

Skift alle 7500 mil/ 6 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2  |
|--------------------------|----------------------|
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b> |

Skift alle 5000 mil/ 4 måneder

## DIFFERENTIALE BAG

Kapacitet: 1,35 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         |  |
|-----------------------------|--|
| <b>Gearlube GL-5 80W-90</b> |  |

Kontroller alle 15000 mil/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2        | PRODUKTANBEFALING 3 |
|---------------------|----------------------------|---------------------|
| <b>SP Gear 5015</b> | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b> |

Kontroller alle 15000 mil/ 12 måneder

| ANVEND              | KLIMA   |
|---------------------|---------|
| Normal (alternativ) | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3   |
|---------------------|---------------------------|-----------------------|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b> |

Kontroller alle 15000 mil/ 12 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1         |  |
|-----------------------------|--|
| <b>Gearlube GL-5 80W-90</b> |  |

Skift alle 15000 mil/ 12 måneder

# LEXUS (USA / CAN) SC Z40 SC 430 (USA) (2003-2003)



| ANVEND              |                            | KLIMA               |
|---------------------|----------------------------|---------------------|
| Krævende            |                            | Arktisk             |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2        | PRODUKTANBEFALING 3 |
| <b>SP Gear 5015</b> | <b>Gearlube RPC 75W-80</b> | <b>SP Gear 1071</b> |

Skift alle 15000 mil/ 12 måneder

| ANVEND                |                           | KLIMA                 |
|-----------------------|---------------------------|-----------------------|
| Krævende (alternativ) |                           | Moderat               |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3   |
| <b>SP Gear 1011</b>   | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b> |

Skift alle 15000 mil/ 12 måneder

| GEAR AUTOMATISK A650E 5/1<br>Kapacitet: 1,8 liter (Servicepåfyldning), Kapacitet: 8,9 liter (Tør efterfyld) |  |         |
|-------------------------------------------------------------------------------------------------------------|--|---------|
| ANVEND                                                                                                      |  | KLIMA   |
| Normal                                                                                                      |  | Moderat |
| PRODUKTANBEFALING 1                                                                                         |  |         |
| <b>SP Matic 4026</b>                                                                                        |  |         |

Kontroller alle 30000 mil/ 24 måneder

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Krævende             |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Matic 4026</b> |  |         |

Kontroller alle 30000 mil/ 24 måneder, skift alle 60000 mil/ 48 måneder

| HYDRAULISK BREMSESYSYSTEM |  |         |
|---------------------------|--|---------|
| ANVEND                    |  | KLIMA   |
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Drauliquid DOT 3</b>   |  |         |

Kontroller alle 15000 mil/ 12 måneder, skift alle 30000 mil/ 24 måneder

| SERVOSTYRING         |                     |                        |
|----------------------|---------------------|------------------------|
| ANVEND               |                     | KLIMA                  |
| Normal               |                     | Moderat                |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3    |
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  | <b>ATF Dexron II-D</b> |

Kontroller alle 15000 mil/ 12 måneder

# LEXUS (USA / CAN) SC Z40 SC 430 (USA) (2003-2003)



## KØLESYSTEM

Kapacitet: 9,9 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 12 EVO**

*Skift alle 30000 mil/ 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*