LEXUS (USA / CAN) GS S190 GS 350 4WD (USA) (2007-2011)



er		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Xedoz FE 5W-30		
		CLIMATE Moderate PRODUCT RECOMMENDATION 2

Change every 5000 miles/ 6 months

Check every 15000 miles/ 18 months

DIFFERENTIAL FRONT Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check every 15000 miles/ 18 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

DIFFERENTIAL REAR
Capacity: 1,35 liter

USE

Normal

PRODUCT RECOMMENDATION 1

SP Gear 1071

Check every 15000 miles/ 18 months

LEXUS (USA / CAN) GS S190 GS 350 4WD (USA) (2007-2011)



TRANSMISSION AUTOMATIC 6/1 Capacity: 10 liter (Dry fill), Capacity: 2,8 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Change every 60000 miles/ 72 months				
HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				
Change every 30000 miles/ 36 months				
COOLING SYSTEM Capacity: 9,1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months