

# LEXUS (USA / CAN) LS XF40 LS 460 2WD (USA) (2014-2017)

**ENGINE 1UR-FSE**

Capacity: 10,2 liter (Dry fill), Capacity: 8,6 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 10000 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 5000 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071***Check every 15000 miles/ 18 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071***Check every 15000 miles/ 18 months, change every 60000 miles/ 72 months***TRANSMISSION AUTOMATIC AA80E 8/1**

Capacity: 10,3 liter (Dry fill), Capacity: 3,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 30000 miles/ 36 months*

# LEXUS (USA / CAN) LS XF40 LS 460 2WD (USA) (2014-2017)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 5000 miles/ 6 months, change every 30000 miles/ 36 months*

## COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*