

LEXUS (USA / CAN) LS XF40 LS 460 4WD (USA) (2008-2013)

**ENGINE 1UR-FSE**

Capacity: 9,8 liter (Dry fill), Capacity: 9 liter (Service fill), Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20****PRODUCT RECOMMENDATION 2****Duranza ECO 5W-20***Change every 5000 miles/ 6 months***DIFFERENTIAL FRONT**

Capacity: 0,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1071***Check every 15000 miles/ 18 months***DIFFERENTIAL REAR**

Capacity: 1,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1071***Check every 15000 miles/ 18 months, change every 60000 miles/ 72 months***TRANSFERBOX AUTOMATIC**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1071***Check every 30000 miles/ 36 months***TRANSMISSION AUTOMATIC AA80F 8/1**

Capacity: 10,7 liter (Dry fill), Capacity: 3,2 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4036***Check every 30000 miles/ 36 months*

LEXUS (USA / CAN) LS XF40 LS 460 4WD (USA) (2008-2013)



HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 5000 miles/ 6 months, change every 30000 miles/ 36 months

COOLING SYSTEM

Capacity: 11,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.